

MSM66101

OLMS-66K Series 16-Bit Microcontroller

GENERAL DESCRIPTION


The MSM66101 is a high performance microcontroller that employs OKI original nX-8/100 CPU core. This chip includes a 16-bit CPU, ROM, RAM, I/O ports, multifunction 16-bit timers, 10-bit A/D converter, serial I/O port, and pulse width modulator (PWM).

FEATURES


- 64K address space for program memory : Internal ROM : 12K bytes
- 64K address space for data memory : Internal RAM : 384 bytes
- High-speed execution
 - Minimum cycle for instruction : 400ns @ 10MHz
- Powerful instruction set : Instruction set superior in orthogonal matrix
 - 8/16-bit data transfer instructions
 - 8/16-bit arithmetic instructions
 - Multiplication and division operation instructions
 - Bit manipulation instructions
 - Bit logic instructions
 - ROM table reference instructions
- Abundant addressing modes : Register addressing
 - Page addressing
 - Pointing register indirect addressing
 - Stack addressing
 - Immediate value addressing
- I/O port
 - Input-output port : 5 ports × 8 bits
(Each bit can be assigned to input or output)
 - Input port : 1 port × 8 bits
- Built-in multifunctional 16-bit timer : 2
 - Following 4 modes can be set for each timer : Auto-reload timer mode
 - Clock output mode
 - Capture register mode
 - Real time output mode
- Serial port : 1 channel (UART mode with baud rate generator)
- 12-bit pulse width modulator : 2
- Watchdog timer
- Transition detector : 4
- 10-bit A/D converter : 8 channels
- Interrupts
 - Nonmaskable : 1
 - Maskable : Internal 10/external 2
- Stand-by function
 - STOP mode : Software clock stop mode
 - HALT mode : Software CPU stop mode
 - HOLD mode : Hardware CPU stop mode

- Package options:
 - 64-pin plastic shrink DIP (SDIP64-P-750-1.78) : (Product name: MSM66101-xxxSS)
 - 64-pin plastic QFP (QFP64-P-1414-0.80-BK) : (Product name: MSM66101-xxxGS-BK)
 - 68-pin plastic QFJ (PLCC) (QFJ68-P-S950-1.27) : (Product name: MSM66101-xxxJS)
 - 64-pin ceramic piggyback (ADIP64-C-750-1.78) : (Product name: MSM66G101VS)
- * The piggyback type is used only for engineering samples.
xxx indicates the code number.

BLOCK DIAGRAM




PIN CONFIGURATION (TOP VIEW)




64-Pin Plastic Shrink DIP

PIN CONFIGURATION (TOP VIEW) (Continued)



64-Pin Plastic QFP

PIN CONFIGURATION (TOP VIEW) (Continued)



NC: No-connection pin

68-Pin Plastic QFJ (PLCC)

PIN DESCRIPTIONS


Symbol	Type	Description
P0.0–P0.7/ AD0–AD7	I/O	P0: 8-bit input-output port. Each bit can be assigned to input or output. AD: Outputs the lower 8 bits of program counter during external program memory fetch, and receives the addressed instruction under the control of PSEN. Also outputs the address and outputs or inputs data during an external data memory access instruction under the control of ALE, RD, and WR.
P1.0–P1.7/ A8–A15	I/O	P1: 8-bit input-output port. Each bit can be assigned to input or output. A: Outputs the upper 8 bits of program counter (PC _{8–15}) during external program memory fetch. Also this pin outputs the upper 8 bits of address during external data memory access instructions.
P2.0–P2.2 P2.3/CLKOUT P2.4/HOLD P2.5/HLDA P2.6 P2.7	I/O	P2: 8-bit input-output port. Each bit can be assigned to input or output. CLKOUT: Output pin for supplying a clock to peripheral circuits. Output frequency range is equal to or twice the system clock. HOLD: Input pin to request the CPU to enter the hardware power-down state. HLDA: HOLD ACKNOWLEDGE: the HLDA signal appears in response to the HOLD signal and indicates that the CPU has entered the power-down state.
P3.0/TxD P3.1/RxD P3.2/ $\overline{\text{INT0}}$ P3.3/ $\overline{\text{INT1}}$ P3.4/TM0IO P3.5/TM1IO P3.6 P3.7	I/O	P3: 8-bit input-output port. Each bit can be assigned to be an input or an output. TxD: Serial port transmitter data output pin. RxD: Serial port receiver data input pin with high impedance. $\overline{\text{INT}}$: Interrupt Request Input pin. TM0IO-TM1IO: One of the following signals is output or input. • Clock at twice the frequency range of the 16-bit timer overflow • Load trigger signal to the capture register input • Setting value output Whether the signal is input or output depends on the mode.
P4.0/TM0CK P4.1/TM1CK P4.2/PWM0 P4.3/PWM1 P4.4 – P4.7/ TRANS0 – 3	I/O	P4: 8-bit input-output port. Each bit can be assigned to an input or an output. TM0CK, TM1CK: Clock input pins of timer 0, timer 1. TRANS: The input pins which sense the rising edge and set the flag. PWM: 12-bit pulse-width modulator output pin.
P5.0 – P5.7/ AI0 – AI7	I	P5: 8-bit input port. AI: Analog signal input pin for A/D converter.

PIN DESCRIPTIONS (Continued)


Symbol	Type	Description
RESOUT	0	Outputs 'H' level when the CPU is in RESET status. Reset to 'L' level in some programs.
ALE	0	Address Latch Enable: The timing pulse to latch the lower 8 bits of the address output from port 0 when the CPU accesses the external memory.
$\overline{\text{PSEN}}$	0	Program Store Enable: The strobe pulse to fetch to external program memory.
$\overline{\text{RD}}$	0	Output strobe activated during a bus read cycle. Used to enable data on to the bus from the external data memory.
$\overline{\text{WR}}$	0	Output strobe during a bus write cycle. Used as write strobe to external data memory.
READY	I	Used when the CPU accesses low speed peripherals.
$\overline{\text{EA}}$	I	Normally set to 'H' level. If set to 'L' level, the CPU fetches the code from external program memory.
$\overline{\text{FLT}}$	I	If $\overline{\text{FLT}}$ is 'H' level, ALE, $\overline{\text{WR}}$, $\overline{\text{RD}}$, $\overline{\text{PSEN}}$ are set to 'H' level when reset. If $\overline{\text{FLT}}$ is set to 'L', ALE, $\overline{\text{WR}}$, $\overline{\text{RD}}$, $\overline{\text{PSEN}}$ are set to floating level when reset.
$\overline{\text{RES}}$	I	RESET input pin.
OSC0	I	Clock oscillation pins
OSC1	0	
$\overline{\text{NMI}}$	I	Nonmaskable interrupt input pin (falling edge)
V_{REF}	I	Reference voltage input pin for A/D converter.
AGND	I	Ground for A/D converter.
V_{DD}	I	System power supply.
GND	I	Ground.

REGISTERS


Accumulator



Control Register (CR)



Pointing Register (PR)



Local Register

	7	0	7	0
ER0	R1		R0	
ER1	R3		R2	
ER2	R5		R4	
ER3	R7		R6	

SFR

Address (HEX)	Name	Symbol	R/W	8/16-bit Operation	Reset
0000	System stack pointer	SSP (ASSP)	R/W	8/16	FFH
0001					FFH
0002	Local register base	LRB (ALRB)			undefined
0003					
0004☆	Program status word	PSWL (APSW)			C8H
0005☆		PSWH			0CH
0006	Accumulator	ACC			00H
0007					00H
0010☆	Standby control register	SBYCON		8	F8H
0011	Watchdog timer	WDT	W		00H/WDT is stopped
0012☆	Peripheral control register	PRPHF	R/W		FDH
0013	Stop code acceptor	STPACP	W		"0"
0018☆	Interrupt request register	IRQ	R/W	8/16	08H
0019☆					0FH
001A☆	Interrupt enable register	IE			08H
001B☆					0FH
001C☆	External linterrupt control register	EXICON		8	FCH
0020	Port 0 data register	P0			undefined
0021	Port 0 mode register	P0IO			00H
0022	Port 1 data register	P1			undefined
0023	Port 1 mode register	P1IO			00H
0024	Port 2 data register	P2			undefined
0025	Port 2 mode register	P2IO			00H
0026☆	Port 2 secondary function control register	P2SF			C7H
0028	Port 3 data register	P3			undefined
0029	Port 3 mode register	P3IO			00H
002A☆	Port 3 secondary function control register	P3SF			C0H
002C	Port 4 data register	P4			undefined
002D	Port 4 mode register	P4IO			00H
002E	Port 4 secondary function control register	P4SF			00H
002F	Port 5	P5	R		—
0030	Timer 0 counter	TM0	R/W	16	00H
0031					00H
0032	Timer 0 register	TMR0			00H
0033					00H
0034	Timer 1 counter	TM1			00H
0035					00H
0036	Timer 1 register	TMR1			00H
0037					00H

☆ indicates that the register has a nonexistent bit.

SFR (Continued)

Address (HEX)	Name	Symbol	R/W	8/16-bit Operation	Reset
0040	Timer 0 control register	TCON0	R/W	8	00H
0041	Timer 1 control register	TCON1			00H
0046☆	Transition detector register	TRANSIT			undefined
0048	Serial port transmission baud rate generator counter	STTM			00H
0049	Serial port transmission baud rate generator register	STTMR			00H
004A☆	Serial port transmission baud rate generator control register	STTMC			0FH
0050☆	Serial port transmission mode control register	STCON			82H
0051	Serial port transmission data buffer register	STBUF	W		undefined
0054	Serial port receiving mode control register	SRCON	R/W		12H
0055	Serial port receiving data buffer register	SRBUF	R		undefined
0056☆	Serial port receiving error register	SRSTAT	R/W		F0H
0058☆	A/D scan mode register	ADSCAN			80H
0060☆ 0061	A/D conversion result register 0	ADCR0	R	8/16	undefined
0062☆ 0063	A/D conversion result register 1	ADCR1			
0064☆ 0065	A/D conversion result register 2	ADCR2			
0066☆ 0067	A/D conversion result register 3	ADCR3			
0068☆ 0069	A/D conversion result register 4	ADCR4			
006A☆ 006B	A/D conversion result register 5	ADCR5			
006C☆ 006D	A/D conversion result register 6	ADCR6			
006E☆ 006F	A/D conversion result register 7	ADCR7			

☆ indicates that the register has a nonexistent bit.

SFR (Continued)

Address (HEX)	Name	Symbol	R/W	8/16-bit operation	Reset
0070	PWM 0 counter	PWMC0	R/W	8/16	00H
0071☆					F0H
0072	PWM 0 register	PWMR0			00H
0073☆					F0H
0074	PWM 1 counter	PWMC1			00H
0075☆					F0H
0076	PWM 1 register	PWMR1			00H
0077☆					F0H
0078☆	PWM 0 control register	PWCON0		8	0CH
007A☆	PWM 1 countrol register	PWCON1			0CH


☆ indicates that the register has a nonexistent bit.

ADDRESSING MODES

The MSM66101 provides independent 64K-byte data and 64K-byte program spaces with various types of addressing modes. These modes are shown below, for both RAM (for data space) and ROM (for program space).


1. RAM Addressing Mode (for data space)

1.1 Register Direct Addressing




1.2 Page Addressing

a) Zero Page




b) Direct Page




1.3 Pointing Register (PR) Indirect Addressing


a) Data Point (DP) Indirect




b) User Stack Pointer (USP) Indirect



c) Index Register (X1, X2) Indirect




1.4 Immediate Addressing




2. ROM Addressing Mode (for program space)


2.1 Direct Addressing




2.2 Simple Indirect Addressing



2.3 Double Indirect Addressing




2.4 Indirect Addressing with 16-bit Offset




MEMORY MAPS

Program Memory Space



Data Memory Space



ABSOLUTE MAXIMUM RATINGS

(Ta = 25°C)

Parameter	Symbol	Condition		Rating	Unit
Supply Voltage	V _{DD}	GND = AGND = 0V		−0.3 to 7.0	V
Input Voltage	V _I			−0.3 to V _{DD} +0.3	
Output Voltage	V _O			−0.3 to V _{DD} +0.3	
Analog Ref. Voltage	V _{REF}			−0.3 to V _{DD} +0.3	
Analog Input Voltage	V _{AI}			−0.3 to V _{REF}	
Power Dissipation	P _D	Ta=85°C per package	64-pin shrink DIP	930	mW
			64-pin QFP	565	
			68-pin QFJ	1120	
		Ta = 85°C per output		50	
Storage Temperature	T _{STG}	—		−55 to +150	°C

RECOMMENDED OPERATING CONDITIONS

Parameter	Symbol	Condition	Range	Unit
Supply Voltage	V _{DD}	f _{OSC} ≤ 10MHz	4.5 to 5.5	V
Memory Hold Voltage	V _{DDH}	f _{OSC} = 0Hz	2.0 to 5.5	
Operating Frequency	f _{OSC}	V _{DD} = 5V ±10%	0 to 10	MHz
Ambient Temperature	Ta	—	-40 to +85	°C
Fan Out	N	MOS load	20	—
		TTL load	P0	
			P1, P2, P3, P4	

ELECTRICAL CHARACTERISTICS

DC Characteristics

(V_{DD} = 5V ± 10%, Ta = -40 to +85°C)

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
"H" Input Voltage 1, 3, 6	V _{IH}	—	2.4	—	V _{DD} +0.3	V
"H" Input Voltage 5, 7			4.0	—	V _{DD} +0.3	
"H" Input Voltage 8			4.2	—	V _{DD} +0.3	
"H" Input Voltage 2			3.6	—	V _{DD} +0.3	
"L" Input Voltage 1, 2, 3, 6	V _{IL}	—	−0.3	—	0.8	
"L" Input Voltage 5, 7			−0.3	—	0.8	
"L" Input Voltage 8			−0.3	—	0.4	
"H" Output Voltage 1, 4	V _{OH}	I _O = −400μA	4.2	—	—	
"H" Output Voltage 2		I _O = −200μA	4.2	—	—	
"L" Output Voltage 1, 4	V _{OL}	I _O = 3.2mA	—	—	0.4	
"L" Output Voltage 2		I _O = 1.6mA	—	—	0.4	
Input Leakage Current 3, 6, 7	I _{IH} /I _{IL}	V _I = V _{DD} /0V	—	—	1/−1	μA
Input Current 5			—	—	1/−20	
Input Current 8			—	—	10/−10	
"H" Output Current 1	I _{OH}	V _O = 2.4V	−2	—	—	mA
"H" Output Current 2			−1	—	—	
"L" Output Current 1	I _{OL}		10	—	—	
"L" Output Current 2			5	—	—	
Output Leakage Current 1, 2, 4	I _{LO}	V _O = V _{DD} /0V	—	—	±2	μA
Input Capacitance	C _I	f = 1MHz	—	5	—	pF
Output Capacitance	C _O	Ta = 25°C	—	7	—	
Analog Reference Power Supply Current	I _{REF}	A/D in operation	—	0.3	2	mA
		A/D stopped	—	0.5	10	μA
Current Consumption (during STOP) *	I _{DDS}	V _{DD} = 2V	—	0.2	10	μA
		—	—	1	100	
Current Consumption (during HALT)	I _{DDH}	f _{OSC} = 10MHz No load	—	6	10	mA
Current Consumption	I _{DD}		—	20	35	

1 : Applied to P0

2 : Applied to P1, P2,P3 and P4

3 : Applied to P5

4 : Applied to ALE, $\overline{\text{PSEN}}$, $\overline{\text{RD}}$, $\overline{\text{WR}}$ and RESOUT5 : Applied to $\overline{\text{RES}}$ and $\overline{\text{NMI}}$ 6 : Applied to READY and $\overline{\text{EA}}$ 7 : Applied to $\overline{\text{FLT}}$

8 : Applied to OSC0


* : V_{DD} or GND for ports serving as the input pin. No-load for any other.

AC Characteristics**• External program memory control**(V_{DD}=5V±10%, Ta=-40 to +85°C)

Parameter	Symbol	Condition	Min.	Max.	Unit
Clock (OSC) Pulse	t _{φW}	—	50	—	ns
ALE Pulse Width	t _{AW}	C _L = 50pF	3t _{φW} -20	—	
$\overline{\text{PSEN}}$ Pulse Width	t _{PW}		4t _{φW} -20	—	
$\overline{\text{PSEN}}$ Pulse Delay Time	t _{PAD}		t _{φW} -20	t _{φW} +20	
Low Address Setup time	t _{AAS}		2t _{φW} -35	2t _{φW} +20	
Low Address Hold Time	t _{AAH}		t _{φW} -20	t _{φW} +40	
High Address Delay Time	t _{AAD}		t _{φW} -20	t _{φW} +40	
High Address Hold Time	t _{APH}		t _{φW} -20	t _{φW} +40	
Instruction Setup Time	t _{IS}		100	—	
Instruction Hold Time	t _{IH}		0	t _{φW} -20	

• External data memory control(V_{DD}=5V±10%, Ta=-40 to +85°C)

Parameter	Symbol	Condition	Min.	Max.	Unit
Clock (OSC) Pulse	t _{φW}	—	50	—	ns
ALE Pulse Width	t _{AW}	C _L = 50pF	3t _{φW} -20	—	
$\overline{\text{RD}}$ Pulse Width	t _{RW}		4t _{φW} -20	—	
$\overline{\text{WR}}$ Pulse Width	t _{WW}		4t _{φW} -20	—	
$\overline{\text{RD}}$ Pulse Delay Time	t _{RAD}		t _{φW} -20	t _{φW} +20	
$\overline{\text{WR}}$ Pulse Delay Time	t _{WAD}		t _{φW} -20	t _{φW} +20	
Low Address Setup Time	t _{AAS}		2t _{φW} -35	2t _{φW} +20	
Low Address Hold Time	t _{AAH}		t _{φW} -20	t _{φW} +40	
High Address Setup Time	t _{AAD}		t _{φW} -20	t _{φW} +40	
High Address Hold Time	t _{ARH}		t _{φW} -20	t _{φW} +40	
High Address Hold Time	t _{AWH}		t _{φW} -20	t _{φW} +40	
Memory Data Setup Time	t _{MS}		100	—	
Memory Data Hold Time	t _{MH}		0	t _{φW} -20	
Data Delay Time	t _{DD}		t _{φW} -20	t _{φW} +40	
Data Hold Time	t _{DH}		t _{φW} -20	t _{φW} +40	



• Serial port control

Master mode


(V_{DD}=5V±10%, Ta=-40 to +85°C)

Parameter	Symbol	Condition	Min.	Max.	Unit
Clock (OSC) Pulse Width	t _{φW}	—	50	—	ns
Serial Clock Pulse Width	t _{SCKW}	—	8t _{φW}	—	
Output Data Setup Time	t _{STMXS}	C _L =50pF	8t _{φW} +40	—	
Output Data Hold Time	t _{STMXH}		6t _{φW} -20	—	
Input Data Setup Time	t _{SRMXS}		2t _{φW} +10	—	
Input Data Hold Time	t _{SRMXH}		50	—	

Slave mode

(V_{DD}=5V±10%, Ta=-40 to +85°C)

Parameter	Symbol	Condition	Min.	Max.	Unit
Clock (OSC) Pulse Width	t _{φW}	—	50	—	ns
Serial Clock Pulse Width	t _{SCKW}	—	8t _{φW}	—	
Output Data Setup Time	t _{TSXS}	C _L =50pF	6t _{φW} +40	—	
Output Data Hold Time	t _{TSXH}		6t _{φW} -20	—	
Input Data Setup Time	t _{SRSXS}		100	—	
Input Data Hold Time	t _{SRSXH}		100	—	



A/D Converter Characteristics

• Operating range

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Power Supply Voltage	V_{DD}	$f_{OSC} \leq 10\text{MHz}$	4.5	—	5.5	V
Analog Reference Voltage	V_R	$V_{AG} = \text{GND} = 0\text{V}$	4.5	—	V_{DD}	
Analog Input Voltage	V_{AI}		V_{AG}	—	V_R	
Analog Reference Power Voltage Resistance	R_R		—	16	—	k Ω
Operating Temperature	T_{op}	$V_{DD} = 5\text{V} \pm 10\%$	-40	—	+85	$^{\circ}\text{C}$

• A/D Converter accuracy

Normal operation mode

 $(V_{DD}=5\text{V} \pm 10\%, f_{OSC}=10\text{MHz}, T_a=-40 \text{ to } +85^{\circ}\text{C})$

Parameter	Symbol	Condition	Min.		Typ.		Max.		Unit
				*		*		*	
Resolution	n	See the recommended circuit. $V_R=V_{DD}$ $V_{AG}=\text{GND}=0\text{V}$ Analog input source impedance $\leq 5\text{k}\Omega$ One channel conversion time $t_C=64\mu\text{s}$	—	—	—	—	10	10	Bit
Absolute Error	E_A		—	—	—	—	+3.0 -3.5	+2.0 -3.5	LSB
Relative Error	E_R		—	—	—	—	± 1.5	± 1.0	
Zero Point Error	E_Z		0	0	—	—	+3.0	+2.0	
Full Scale Error	E_F		-0.5	-1.0	—	—	-3.5	-3.5	
Differential Linearity Error	E_D		—	—	—	—	+3.0	+2.0	
Crosstalk	E_C		—	—	± 0.5	± 0.5	—	—	

* $V_{DD}=5\text{V}$, $T_a=25^{\circ}\text{C}$


HALT/HOLD operation mode

 $(V_{DD}=5\text{V} \pm 10\%, f_{OSC}=10\text{MHz}, T_a=-40 \text{ to } +85^{\circ}\text{C})$


Parameter	Symbol	Condition	Min.		Typ.		Max.		Unit
				*		*		*	
Resolution	n	See the recommended circuit. $V_R=V_{DD}$ $V_{AG}=\text{GND}=0\text{V}$ Analog input source impedance $\leq 5\text{k}\Omega$ One channel conversion time $t_C=64\mu\text{s}$	—	—	—	—	10	10	Bit
Absolute Error	E_A		—	—	—	—	+2.0 -3.5	+1.0 -2.0	LSB
Relative Error	E_R		—	—	—	—	± 1.0	± 0.5	
Zero Point Error	E_Z		+0.5	+0.5	—	—	+2.0	+1.0	
Full Scale Error	E_F		-1.0	-1.5	—	—	-3.5	-2.0	
Differential Linearity Error	E_D		—	—	—	—	+2.0	+1.0	
Crosstalk	E_C		—	—	± 0.5	± 0.5	—	—	

* $V_{DD}=5\text{V}$, $T_a=25^{\circ}\text{C}$

• Recommended circuit



• A/D Converter conversion characteristics 1



Absolute error (E_A)

The absolute error indicates a difference between actual conversion and ideal conversion, excluding a quantizing error. The absolute error of the A/D converter gets larger as it approaches the zero point or full scale. (See to Conversion Characteristics Diagram 1.)


Relative error (E_R)

The relative error indicates a deviation from a line which connects the center point of the zero point conversion width with that of the full scale conversion width, excluding a quantizing error.


The relative error of this A/D converter is almost due to a differential linearity error.

Zero point error (E_Z) and full scale error (E_F)

The zero point error and full scale error indicate a difference between actual conversion and ideal conversion at the zero point and full scale, respectively. (See Conversion Characteristics Diagram 1.)

• A/D Converter conversion characteristics 2 (Temperature Characteristics)

**Conversion
Characteristics
Diagram 2-1**



**Conversion
Characteristics
Diagram 2-2**


Differential linearity error (E_D)

The differential linearity error indicates a difference between the actual conversion width (actual step width) and ideal value (1LSB).

With this A/D converter, a voltage for actual conversion is shifted and the inclination of a voltage is changed, with changes of temperature (see Conversion Characteristics Diagram 2-1). Specifications described in the foregoing tables are established from Eta shown in Conversion Characteristics Diagram 2-1. Conversion Characteristics Diagram 2-2 shows temperature characteristics of differential linearity error of E_S .

PACKAGE DIMENSIONS

(Unit : mm)




Notes for Mounting the Surface Mount Type Package

The SOP, QFP, TSOP, SOJ, QFJ (PLCC), SHP and BGA are surface mount type packages, which are very susceptible to heat in reflow mounting and humidity absorbed in storage.

Therefore, before you perform reflow mounting, contact Oki's responsible sales person for the product name, package name, pin number, package code and desired mounting conditions (reflow method, temperature and times).

(Unit : mm)




Notes for Mounting the Surface Mount Type Package

The SOP, QFP, TSOP, SOJ, QFJ (PLCC), SHP and BGA are surface mount type packages, which are very susceptible to heat in reflow mounting and humidity absorbed in storage.

Therefore, before you perform reflow mounting, contact Oki's responsible sales person for the product name, package name, pin number, package code and desired mounting conditions (reflow method, temperature and times).

(Unit : mm)




Notes for Mounting the Surface Mount Type Package

The SOP, QFP, TSOP, SOJ, QFJ (PLCC), SHP and BGA are surface mount type packages, which are very susceptible to heat in reflow mounting and humidity absorbed in storage.

Therefore, before you perform reflow mounting, contact Oki's responsible sales person for the product name, package name, pin number, package code and desired mounting conditions (reflow method, temperature and times).

ADIP64-C-750-1.78



The SOP, QFP, TSOP, SOJ, QFJ (PLCC), SHP and BGA are surface mount type packages, which are very susceptible to heat in reflow mounting and humidity absorbed in storage. Therefore, before you perform reflow mounting, contact Oki's responsible sales person for the product name, package name, pin number, package code and desired mounting conditions (reflow method, temperature and times).