



SoftTip® – SpO₂ sensor for maximum patient comfort and highest safety

**Robust
Economic**



Durable and reliable

EnviteC SoftTip® SpO₂ sensors

- Maximum safety
- Easy handling and optimal cleaning
- Maximum resistance to mechanical stress
- High wearing comfort
- Exceptional measurement reliability
- Outstanding cost efficiency
- DIN EN ISO 17664 compliant





SoftTip® – highest comfort with remarkable measurement reliability

EnviteC solutions bring clear advantages to SpO₂ sensor technology

Safety and cost efficiency

With the SoftTip®, EnviteC offers an uncompromising solution: a long-term reusable finger sensor that offers easy cleaning by submersion in cleaning liquid and withstands maximum mechanical stress. This means a rapid return on investment and huge cost savings compared with alternative solutions.

Comfortable and precise

The unique product design guarantees extraordinarily high patient comfort and exceptionally accurate measurement results. Compatibility with common monitoring devices from all well-known manufacturers is guaranteed.

The right size for all applications

The SoftTip® sensor is available in three sizes. This ensures that a suitable sensor is available for every patient, from children to adults.



Robust and reliable

This sheath-like designed sensor is not only resilient to immersion, but also extremely resistant to mechanical stress and resulting failure. The life of the product is three times longer than comparable conventional finger sensors.

Optimum handling and maximum comfort







Thanks to the ergonomic design, the number of false alarms is greatly reduced. In addition, special silicon - tested and proven for its biocompatibility - virtually eliminates the possibility of allergic skin reactions.







Disinfectants and cleaning agents







All common disinfectants and cleaning agents based on aldehydes, alcohol, amines, lye or quaternary ammonium compounds are suitable for the cleaning and disinfection of SoftTip® SpO₂ sensors.







Safety that you can rely on







EnviteC products are used and trusted throughout the world. Our fully moulded silicon sensor guarantees maximum safety standards for patients and medical staff.

Compatible with	BCI		CSI		Datex	
Product number R, RM, RS*	3222-12	3282-9	3282-30	3282-36	3512-9	3512-20
Cable length (cm)	120	90	300	300	90	200
Plug	C 03	C 08	C 08	C 31	C 01	C 01
*R = SoftTip® large *RM = SoftTip® medium *RS = SoftTip® small						

Compatible with	Datex	Datex-Ohmeda	EnviteC		HP/Philips	
Product number R, RM, RS*	3512-40	3513-30	3225	3226	3227	2414-15
Cable length (cm)	300	300	120	120	120	150
Plug	C 14	C 64	C 44	C 03	C 45	C 19
*R = SoftTip® large *RM = SoftTip® medium *RS = SoftTip® small						

Compatible with	HP/Philips		Mindray	Minolta	Nellcor	
Product number R, RM, RS*	2414-30	2412	3213-9	2182-3	3212-9	3212-31
Cable length (cm)	300	300	90	30	90	300
Plug	C 19	C 17	C 05	C 45	C 05	C 05
*R = SoftTip® large *RM = SoftTip® medium *RS = SoftTip® small						

Compatible with	Nellcor	Nihon-Kohden		Nonin		
Product number R, RM, RS*	3214-12	2202-1	2203-16	3012	3012-30	3013
Cable length (cm)	120	300	160	90	300	90
Plug	C 49	C 18	C 10	C 04	C 04	C 49
*R = SoftTip® large *RM = SoftTip® medium *RS = SoftTip® small						

Compatible with	Nonin	Novamatrix		Ohmeda		
Product number R, RM, RS*	3013-30	3262	3262-9	3412-10	3412	3412-9
Cable length (cm)	300	300	90	100	300	90
Plug	C 49	C 21	C 01	C 22	C 22	C 01
*R = SoftTip® large *RM = SoftTip® medium *RS = SoftTip® small						

 Made in Germany

EnviteC-Wismar GmbH
a Honeywell Company
 Alter Holzhafen 18, 23966 Wismar, Germany
 Phone: +49 (0) 3841 / 360-1
 Phone: +49 (0) 3841 / 360-200 Sales
 Fax: +49 (0) 3841 / 360-222

Internet: www.envitec.com
E-mail: info@envitec.com

ENVITEC
 by Honeywell