


# CERLED<sup>®</sup>

## SMD Chip Detector

Selective Photodiode  
SR 10 SPD 525 - 0.9 -H\*

\*RoHS-Compliant



### Description

Wavelength range: green;


GaP technology.

Ideal for sensor applications, alarm systems,  
light barriers, special sensors for automotive  
industry.

Available in 8 mm blister tape.

### Features and Benefits

- ▶ Narrow bandwidth and high spectral sensitivity in the green-red visible range (450...570 nm)
- ▶ Low cost chip based on GaP
- ▶ Chip on PCB, surface mounting device
- ▶ End - to - end and side - to - side stackable down to a pitch of 1.6 mm




### Maximum Ratings at 25° C

Storage temperature	T <sub>st</sub>	-25° C to 120° C
Operating temperature	T <sub>op</sub>	-25° C to 80° C
Soldering temperature	T <sub>solid</sub> (5 s)	240° C

### Characteristics at 25° C

	Symbol	Min.	Typ.	Max.	Unit	Conditions
Active area	A		0.73		mm <sup>2</sup>	
Peak sensitivity wavelength	$\lambda_p$	510	525	535	nm	V <sub>R</sub> = 0 V
Spectral range at 0.5 max.	$\lambda_{0.5}$	480		560	nm	V <sub>R</sub> = 0 V
Responsivity at $\lambda_p$	S <sub><math>\lambda</math></sub>	0.15	0.25	0.38	A/W	V <sub>R</sub> = 0 V
Spectral bandwidth at 50 %	$\Delta\lambda_{0.5}$		75		nm	V <sub>R</sub> = 0 V
Dark current	I <sub>D</sub>		5	30	pA	V <sub>R</sub> = 1 V, E <sub>a</sub> = 0
Reverse voltage	V <sub>R</sub>	5			V	I <sub>R</sub> = 10 $\mu$ A
Temperature coefficient of I <sub>D</sub>	TCI <sub>D</sub>		4.7		%K	

Figure 1



Orientation of taped parts: anode to perforation

**Excelitas Technologies**  
**European Customer**  
**Support for LED Solutions**  
 Luitpoldstrasse 6  
 85276 Pfaffenhofen, Germany  
 Telephone: (+49)8441-8917-0  
 Fax: (+49)8441-71910  
[generalinquiries@excelitas.com](mailto:generalinquiries@excelitas.com)

**European Headquarters**  
 Wenzel-Jaksch-Strasse 31  
 65199 Wiesbaden, Germany  
 Telephone: (+49)611-492-269  
 Fax: (+49)611-492-170

**North America**  
**Customer Support Hub**  
 22001 Dumberry Road  
 Vaudreuil-Dorion, Québec  
 Canada J7V 8P7  
 Telephone: (+1) 450-424-3300  
 (+1) 866-574-6786 (toll-free)  
 Fax: (+1) 450-424-3345

**Asia Customer Service Hub**  
 47 Ayer Rajah Crescent #06-12  
 Singapore 139947  
 Telephone: (+65)6775-2022  
 (+65)67704-366  
 Fax: (+65)6775-1008

**EXCELITAS**  
 TECHNOLOGIES

For a complete listing of our global offices, visit [www.excelitas.com](http://www.excelitas.com)

©2011 Excelitas Technologies Corp. All rights reserved. The Excelitas logo and design are registered trademarks of Excelitas Technologies Corp. CERLED® is a trademark of Excelitas Technologies Corp. or its subsidiaries, in the United States and other countries. All other trademarks not owned by Excelitas Technologies or its subsidiaries that are depicted herein are the property of their respective owners. Excelitas reserves the right to change this document at any time without notice and disclaims liability for editorial, pictorial or typographical errors.  
 600082\_02 DTS0407