

646GE & 646VE
SHIPPING WT.
APPROX. 44 OZ.
(1247 GRAMS)

646PE
SHIPPING WT.
APPROX. 39 OZ.
(1105 GRAMS)

基本特性:
 U.L./CSA
 NEMA: 4,7,9,13
 防爆型
 温度 - 34至71°C
 外部设定

646GE

接口尺寸	1/4"
接口材料	铝合金
隔膜材料	聚丁钠橡胶

最大允许压力 (KG)	设定压力范围 (KG)	压力开关型号	
		SPDT	DPDT
34.48	0.08~1.19	646GE1	646GEM1
206.90	0.41~4.90	646GE2	646GEM2
206.90	0.83~9.79	646GE11	646GEM11
206.90	2.07~24.48	646GE3	646GEM3
206.90	20.69~65.17	646GE5	646GEM5

646PE


接口尺寸	1/4"
接口材料	铝合金
活塞型	聚丁钠橡胶

最大允许压力 (KG)	设定压力范围 (KG)	自由引线		带端子	
		自由引线	带端子	自由引线	带端子
137.93	1.03~13.03	646PE12	6401PE12	646PEM12	6401PEM12
206.90	10.34~93.10	646PE15	6401PE15	646PEM15	6401PEM15
344.83	13.79~193.10	646PE21	6401PE21	646PEM21	6401PEM21
517.24	137.93~293.10	646PE31	6401PE31	646PEM31	6401PEM31
689.65	137.93~413.79	646PE41	6401PE41	646PEM41	6401PEM41


接点容量

电压	电流	
	SPDT Res.	DPDT Res.
125AC~50/60Hz	15	5
250AC~50/60Hz	15	5
480AC~50/60Hz	15	—
125DC	—	—

SPDT
COLOR OF LEADS



DPDT
COLOR OF LEADS



OPTIONAL FEATURES:

"A" = Viton O-ring
 "F" = Ethylene Propylene O-ring