



## ULTRA MINIATURE (7x5 mm) SMD TCXO/VC-TCXO IN LEADLESS PACKAGE - TC75 Series

### FEATURES

- RoHS Compliant (Pb-Free), Tight Stability over Wide Temperature Range
- Voltage Control Option for Electric Frequency Adjustments
- Leadless Chip Carrier (LCC) Ultra Small Package, Industry de factor Standard Footprint
- Small Size, Low Profile, Light Weight and Low Power Consumption

### SPECIFICATIONS

<b>Frequency Range</b>	10 MHz to 27 MHz
<b>Standard Frequency</b>	12.6/12.8/13.0/14.4/14.85/16.8/19.2/19.44/19.68/19.8 MHz
<b>Input Voltage (Vcc)</b>	2.8 - 5.0 VDC (A=5.0V±5%; B=3.3V±5%; C=3.0V±5%; D=2.8V±5%)
<b>Input Current</b>	2.0 mA Maximum (at 3V, 25°C)
<b>Storage Temperature</b>	-40°C to 85°C
<b>Frequency Stability vs Temp. Temperature Range</b>	015 = ±1.5 ppm; 020 = ±2 ppm; 025 = ±2.5 ppm; 050 = ±5 ppm A = 0°C to 70°C; B = -40°C to 85°C; F = 0°C to 50°C; H = -30°C to 75°C
<b>Standard Stability</b>	025H = ±2.5 ppm / -30°C to 75°C
<b>Frequency Stability vs Vcc</b>	±0.2 ppm Maximum / Vcc ± 5%
<b>Frequency Stability vs Load</b>	±0.2 ppm Maximum / 10 kOhms or 10 pF ±10%
<b>Aging</b>	±1 ppm Maximum per year @25°C
<b>Output Load</b>	10 kOhms or 10 pF ±10%
<b>Output Waveform</b>	Clipped Sine wave
<b>Output Level</b>	1.0Vp-p Minimum for Vcc=5.0V; 0.8Vp-p Minimum for Vcc=3.3V
<b>Controllable Frequency Option</b>	±10 ppm Minimum over control voltage range
<b>Control Voltage (Vc)</b>	2.5±2.0 VDC for Vcc = 5 VDC; 1.65±1.5 VDC for Vcc = 3.3 VDC
<b>Setability of Vc at Fnom, 25°C</b>	2.5±0.5 V DC for 5.0V part; 1.65±0.4 VDC for 3.3V part

### Creating a Part Number

**TC75-19M800-B V 015 B**

Product Series	TC75	Operating Temperature Range: A = 0 to 70°C
Frequency	19M	Frequency Stability: B = -40 to 85°C
Supply Voltage: A = 5.0V	B = 3.3V	H = -30 to 75°C
	V	X = Customized Temp Range
	blank	015 = ±1.5 ppm
		020 = ±2 ppm
		025 = ±2.5 ppm

### OUTLINE DRAWING

